

Beräkning av bländning enligt UGR

| p Tak | 80 | 70 | 70 | 50 | 50 | 80 | 70 | 70 | 50 | 50 | |
|--|-----|------------------------------------|------|------|------|------|------------------------------------|------|------|------|------|
| p Vägg | 60 | 50 | 30 | 50 | 30 | 60 | 50 | 30 | 50 | 30 | |
| p Golv | 30 | 20 | 20 | 20 | 20 | 30 | 20 | 20 | 20 | 20 | |
| Rumsstorlek X Y | | Blickriktning tvärs till tvärsaxel | | | | | Blickriktning längs till tvärsaxel | | | | |
| 2H | 2H | 18.8 | 20.6 | 21.3 | 20.9 | 21.5 | 18.8 | 20.6 | 21.3 | 20.9 | 21.5 |
| 2H | 3H | 18.7 | 20.6 | 21.2 | 20.9 | 21.4 | 18.7 | 20.6 | 21.2 | 20.9 | 21.4 |
| 2H | 4H | 18.7 | 20.6 | 21.2 | 20.9 | 21.4 | 18.7 | 20.6 | 21.2 | 20.9 | 21.4 |
| 2H | 6H | 18.7 | 20.6 | 21.1 | 20.9 | 21.4 | 18.7 | 20.6 | 21.1 | 20.9 | 21.4 |
| 2H | 8H | 18.8 | 20.6 | 21.2 | 21.0 | 21.4 | 18.8 | 20.6 | 21.2 | 21.0 | 21.4 |
| 2H | 12H | 18.8 | 20.7 | 21.1 | 21.0 | 21.4 | 18.8 | 20.7 | 21.1 | 21.0 | 21.4 |
| 4H | 2H | 18.6 | 20.5 | 21.0 | 20.8 | 21.3 | 18.6 | 20.5 | 21.0 | 20.8 | 21.3 |
| 4H | 3H | 18.6 | 20.5 | 20.9 | 20.8 | 21.2 | 18.6 | 20.5 | 20.9 | 20.8 | 21.2 |
| 4H | 4H | 18.6 | 20.5 | 20.9 | 20.9 | 21.2 | 18.6 | 20.5 | 20.9 | 20.9 | 21.2 |
| 4H | 6H | 18.7 | 20.6 | 21.0 | 21.0 | 21.3 | 18.7 | 20.6 | 21.0 | 21.0 | 21.3 |
| 4H | 8H | 18.7 | 20.7 | 21.0 | 21.1 | 21.4 | 18.7 | 20.7 | 21.0 | 21.1 | 21.4 |
| 4H | 12H | 18.8 | 20.8 | 21.0 | 21.2 | 21.4 | 18.8 | 20.8 | 21.0 | 21.2 | 21.4 |
| 8H | 4H | 18.5 | 20.5 | 20.8 | 20.9 | 21.2 | 18.5 | 20.5 | 20.8 | 20.9 | 21.2 |
| 8H | 6H | 18.7 | 20.7 | 20.9 | 21.1 | 21.3 | 18.7 | 20.7 | 20.9 | 21.1 | 21.3 |
| 8H | 8H | 18.8 | 20.8 | 21.0 | 21.2 | 21.4 | 18.8 | 20.8 | 21.0 | 21.2 | 21.4 |
| 8H | 12H | 18.9 | 20.9 | 21.0 | 21.4 | 21.5 | 18.9 | 20.9 | 21.0 | 21.4 | 21.5 |
| 12H | 4H | 18.5 | 20.5 | 20.7 | 20.9 | 21.1 | 18.5 | 20.5 | 20.7 | 20.9 | 21.1 |
| 12H | 6H | 18.7 | 20.7 | 20.8 | 21.1 | 21.3 | 18.7 | 20.7 | 20.8 | 21.1 | 21.3 |
| 12H | 8H | 18.8 | 20.8 | 20.9 | 21.3 | 21.4 | 18.8 | 20.8 | 20.9 | 21.3 | 21.4 |
| Variation av åskådarposition för tvärsaxel S | | | | | | | | | | | |
| S = 1.0H | | +5.0 / -4.3 | | | | | +5.0 / -4.3 | | | | |
| S = 1.5H | | +7.7 / -4.7 | | | | | +7.7 / -4.7 | | | | |
| S = 2.0H | | +9.7 / -5.0 | | | | | +9.7 / -5.0 | | | | |
| Standardtabell | | BK01 | | | | | BK01 | | | | |
| Korrektionsfaktor | | 2.6 | | | | | 2.6 | | | | |

Korrigerade bländindikeringar relaterade till totalt ljusflöde